Technical data sheet

Junction box T350, plug-in seal, elevated cover

Item number: 2007718





Junction box for the connection of cables and lines indoors and in protected outdoor areas. Rectangular design with plug-in seals. Suitable for wall and ceiling mounting, on mounting panels and threads in the floor. With the option to fasten inside and to mount via the corner domes. High, transparent cover with quick lock, sealable. Made from halogen-free and UV-resistant materials.

With hat profile rail.

Junction box according to DIN EN 60670. Flame-resistant to DIN EN 60695/2/11, test temperature 650 °C. Impact resistance IK05 according to DIN EN 50102. Clear internal dimensions: 267x182x127 mm





Polypropylene / polycarbonate

Master data


2007718
Junction box
with raised cover
OBO
285x201x139
Light grey; RAL 7035
Polypropylene / polycarbonate
1
Piece
72.76 kg
kg/100 pc.
3,2881 kg COe / 1 Piece

Technical data sheet

Junction box T350, plug-in seal, elevated cover

Item number: 2007718





Length	285 mm
Width	201 mm
Height	137 mm

Technical data

Expandable	yes
No of entries	24
Type of insertion	24 Plug-in seal
51	Cable
Type of entry	Miscellaneous
Type of housing penetration	
Measured insulation voltage Vi	500 V
Equipment	Without
Cover	Not transparent
Cover fastening	Screwed
Entry from rear	yes
Entries	16xM328xM40
Explosion-tested version	no
Flame-resistant	acc. to VDE 0471/DIN 695 Part 2-1, test temperature 650°C
Shape	Rectangular
Maintain electrical functions	Without
For Ex zone	Without
For Ex zone gas	Without
For Ex zone dust	Without
Fibre-glass reinforced	yes
Halogen-free	yes
Clear internal dimensions	267x182x127 mm
With screening	no
with lid	yes
Mounting type	Wall/ceiling mounting
Nominal voltage	500 V
Sealable	yes
Protection rating	IP66
Protection rating IK code	IK05.
Permitted temperature range, max.	60 °C
Permitted temperature range, min.	-5 °C
Weatherproof	no