## **Technical data sheet Empty housing X 01**

**Item number: 2005590** 





Master data

Junction box for the connection of cables and lines indoors and in outdoor areas. Square design without entries. Suitable for wall and ceiling mounting with the option to fasten outside, inside or to mount via the corner domes. Particularly impact resistant with IK09. Cover with quick lock, sealable. Made from halogen-free and UV-resistant materials.

Junction box according to EN 60670. Impact resistance IK09 according to EN 50102. Protection rating IP67 according to EN 60529.

















0,629 kg COe / 1 Piece



Polycarbonate

CO Footprint (GWP) Cradle-to-Gate


2005590
Empty Enclosure
OBO
95x95x60
Graphite black; RAL 9011
Polycarbonate
1
Piece
15.6 kg
kg/100 pc.

## Technical data sheet Empty housing X 01





## Length Width 95 mm Height 60 mm



## Technical data

Extension option	no
Cover fastening	Screwed
Shape	Square
Suitable for outdoor use	yes
Clear internal dimensions	85x85x45 mm
with lid	yes
Mounting type	Surface-mounted
Protection rating	IP67
Protection rating IK code	IK09
Protection class	II
Permitted temperature range, max.	60 °C
Permitted temperature range, min.	-5 °C
Weatherproof	yes