
Technical data sheet

Roof hook for PV module mounting, screwable profile, tiled roof

Item number: 5901404



Roof hook to mount photovoltaic modules on pitched roofs in combination with the TP 45 support profile. Suitable for tiled roofs. Screwable fastening on the support profile. Mounting on rafters with TKS wafer-head screws. The roof hook can be adjusted horizontally as well as vertically continuously via glands, correctTorx 40 key. Height adjustment in the range of the roof slat between 40–54 mm, side adjustment option up to 76 mm, height adjustment of the support profile up to 18 mm.

CE

A2	Stainless steel
2B	Bright, treated

Master data


Item number	5901404
Type	DHU T A2
Description 1	Roof hook, screwable profile
Description 2	for pitched roof system
Manufacturer	OBO
Dimension	120x186x150
Colour	stainless steel
Material	Stainless steel 1.4301
Surface Surface standard	Bright, treated
Smallest sales unit	10
Unit of quantity	Piece
Weight	100.7 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to-Gate	6,4247 kg CO2e / 1 Piece

Technical data sheet

Roof hook for PV module mounting, screwable profile, tiled roof

Item number: 5901404

Dimensions



Width	120 mm

Technical data

Material thickness	8 mm
With fastening material	no
With mounting plate	yes
Angle of inclination, max.	90 °
Angle of inclination, min.	0 °
Adjustable	yes
Suitable for fastening photovoltaic roof/facade fastening	Pitched roof fastening
Suitable for roof material	Roof tile
Wide fastening plate	75 mm
Fastening plate, length	120 mm
Height-fastening plate	36 mm
Penetration of roof necessary	yes
Alignment	Horizontal
Anchoring	Bolts